

Kelin sabon samfuri ne da aka haɓaka bayan kawancen tayal ɗin tayal mai launin ruwan hoda, ba wai kawai yana riƙe da nau'in ƙoshin tayal mai launi na ruwa ba, yana haɓaka aikin samfurin, amma kuma yana sa gini ya fi sauƙi kuma ya fi dacewa. Rubutu mai laushi, yana nuna salon kayan ado mai ƙarancin maɓalli. Iri-iri na launuka, sanya wurin adonku ya haskaka. Eco-friendly epoxy resin subbase course bar samfurin ku ya zama mai hana ruwa, juriya, kwaƙƙwaran ƙira da kuma tabbatar da danshi. Yashi na dabi'a da aka kirƙira a babban zafin jiki yana sa launi ya fi na halitta da kyau kuma baya dusashewa. Hakanan, yana da haske kamar ain bayan cluing ba tare da rawaya ko canza launin ba. Bugu da ƙari, haɗin haɗin gwiwa yana kama da dacewa da tayal yumbura, kamar dai yanayin kanta.

Samfurin na [China Liquid Sealant manufacturer](#) za a iya amfani da mafi alhɛri a cikin gidajen abinci na yumbu tayal, dutse, gilashi, mosaic tayal a bango ko gari a gidan wanka, kitchen, ɗakin kwana da sauransu. Ostiraliya na haɗin gwiwar bincike da samfuran haɓaka don samar da ingantaccen aiki, kuma ta hanyar Cibiyar Nazarin Kimiyya ta Sinanci jagorar kula da ingancin dabaru, don tabbatar da ingancin samfuran. [Kelin epoxy gap filler s mai haɓakawa](#) don samar muku da kayayyaki masu inganci.



Launuka iri-iri don zaɓinku. Hakanan samar da launuka na al'ada.

- Gray 1#
- Gray 2#
- Gray 3#
- Gray 4#
- Gray 5#
- Gray 6#
- Gray 7#
- Gray 8#
- Gray 9#
- Cement Gray
- Dull Gray
- Silver Gray
- Metal Gray
- Luxury Silver
- Glacier White
- Calaeatta
- Pearl Gold
- Slate Gray
- Terra Brown
- Greyish Green
- Yellow Gray
- Soft Khaki
- Yellowish Brown
- Olive Brown
- Brownness
- Dark Brown
- Reddish Brown
- Rock Bslack



Samar da Maganin Tazarar Daki Gabaɗaya



Takaitaccen Tsarin Gina



01 Clean the tiles and keep it dry



02 Polish with tile wax except the glazed tile



03 Open & Watch, both sides can extruded meanwhile



04 Screw on the nozzle, put on the grout gun



05 Inclined cut the top of the nozzle in 45°



06 Squeeze out 60-80cm long grout in the forepart



07 Evenly squeeze out the tile agent along the gap



08 Press the grout with professional glue-press tools



09 Don't touch in 4-5 hours and remove excess grout then.



10 Keep the tiles dry in 24 hours

Kayan aikin Matsawa na Haɗin gwiwa



Two Component Caulking Gun



02
Cutter Knife



03
Pointing trowel



04
Brush



05
Forming Stick



06
Perching Knife



07
Masking Tape



08
Stainless Steel Ball



09
Cleaning Awl

Amfanin Kamfanin



Bayanin Masana'antu



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

Takaddun shaida

